

# Java Cheat Sheet

---

Dr. Mark R. Floryan

September 3, 2018

## 1 JAVA: GENERAL THINGS TO REMEMBER

1. All code must be inside of a class definition (except import and package statements).
2. Every line of code must end with a semi-colon. This excludes lines that formulate "blocks", like `if()`, `while()`, or class declarations.
3. The name of the class in a file must match the name of the file. For example, `"public class LinkedList"` must be in a file called `"LinkedList.java"`
4. Classes can contain a method `"public static void main(String[] args)"` as an entry point to the whole program.
5. Whitespace does NOT matter in java. The compiler will completely ignore all whitespace.

## 2 PRIMITIVE DATA TYPES

The primitive variable types are:

```

1  int x = 5; //integers
   double d = 3.4; //decimal values
3  char c = 'h'; //characters. Use single quotes.
   boolean b = false; //true or false
5
   /* Other much less commonly used */
7  byte b = 24b;
   short s = -8s;
9  long l = 2000000;
   float = 4.567;

```

Some examples of using these data types include:

```

   int x;           //automatically set to 0 by default
2  x++;           //increment integer by 1
   x--;           //decrement integer by 1
4
   int z = 14;
6
   int total = (x + z) * x;   //expressions
8  int remainder = x % z;    //remainder after x / z

10 /* Boolean operators */
   boolean b1 = false;
12 boolean b2 = true;
   boolean result;
14
   result = b1 && b2; //logical AND
16 result = b1 || b2; //logical OR
   result = !b1;     //logical negation

```

### 3 INPUT OUTPUT

Input from the keyboard can be done like this:

```

1  Scanner in = new Scanner(System.in); //make a scanner object
   int x = in.nextInt();                //read int from keyboard
3  double y = in.nextDouble();          //read double from keyboard
   float f = in.nextFloat();            //read float from keyboard
5  boolean b = in.nextBoolean();        //read bool from keyboard
   long l = in.nextLong();              //read long from keyboard
7  String s = in.next();                 //read string from keyboard

```

Input from a file can be done like this:

```
1 BufferedReader in =
    new BufferedReader(new FileReader("inputfile.txt"));
3 String text = in.readLine();    //reads the next line
  in.close();
```

Output to the console is done like this:

```
    //prints text concatenated with x
2 System.out.print("The answer is " + x);

4 //prints and moves cursor to next line
  System.out.println("something else");
```

Output to a file can be done like this:

```
1 PrintWriter outFile =
    new PrintWriter(new FileWriter("outputfile.txt"));
3 outFile.print("Hello ");
  outFile.println("world");
5 outFile.close();
```

## 4 STRINGS

Strings are reference types in Java (so they are NOT primitives).

```
1 String s1 = "Hello";           //example string
  String s2;                     //"" empty string by default
3 String s3 = new String("Hi");  //Also makes a string
```

Common operators on strings include:

```
1 String result;

3 result = s1 + s2;    //"hi " + "there" = "hi there"
  s1.length();        //returns length of string
5 s1.charAt(2);        //accesses the char at position 2 (indexed from 0)
  s1.substring(1,3);  //part of string from index 1 to 3 (exclusive)
7 s1.equals(s2);       //compare strings using this structure
  s1.toUpperCase();   //returns the string as all uppercase
9 s1.toLowerCase();   //returns the string as all lowercase
```

## 5 CONVERTING BETWEEN DATA TYPES

In Java, we often need to convert between different types of variables. Here are some common conversions:

```
1  /* int (or any other primitive) to string */
   int x = 5;
3  String s = "" + x;  //" + variable concatenates as a string

5  /* String version of number to int or double */
   int i = Integer.parseInt("123");          //converts string "123" into integer
7  double d = Double.parseDouble("3.14")    //converts string "3.14" into double

9  /* dividing integers does integer division */
   int x1 = 3;
11 int x2 = 5;
   double result = x1 / x2;                  // 3/5=(int)0.6 = 0
13 result = (double)x1 / (double)x2;        //0.6

15 /* double to int */
   double x = 3.467;
17 int y = (int)x;                          //y is 3, decimal truncated
```

## 6 ARRAYS

Three primary ways to instantiate arrays:

```
1  double[] dArray = new double[5];          //know the size, but not contents
   int[] oddNumbers = {1,3,5,7,9};          //know the contents already
3
   int x;
5  /* Stuff here */
   String[] sArray = new String[x];         //use variable to initialize array
7
   int[][] = new int[5][4];                 //two-dimensional array
```

Some common things we do with arrays include:

```
   x[3] = 5;    //Access array at position 3, set to 5.
2  x.length;    //get the number of elements in array

4  /* How to loop through an array */
```

```
    for(int i=0; i<x.length; i++){  
6      System.out.println(x[i]);  
    }
```

## 7 JAVA MATH LIBRARY

Java contains several functions inside the Math class that are useful. Among them:

```
1  Math.abs(x);           //absolute value of x  
   Math.max(a,b);       //larger of a and b  
3  Math.min(a,b);       //smaller of a and b  
   Math.sin(theta);     //sin trig function  
5  Math.cos(theta);     //cos trig function  
   Math.tan(theta);     //tangent trig function  
7  Math.toRadians(deg); //convert deg to radians  
   Math.toDegrees(rad); //convert rad to degrees  
9  Math.exp(x);         //raises e^x  
   Math.log(x);         //natural logarithm  
11 Math.pow(a,b);       //raise a to power of b  
   Math.sqrt(a);       //square root of a  
13 Math.E;              //value of constant e  
   Math.PI;            //pi
```